



Essential Smartbright LED Batten

BN068C LED12/WW L1200 TH G2

Essential Smartbright LED Batten, 13 W, 1200 lm, 3000 K, Wide beam

Whether for a new building or renovation of an existing space, customers want lighting solutions that provide quality of light and substantial energy and maintenance savings. This new batten range of LED products can be used to replace traditional battens with fluorescent lamps. The process of selecting, installing and maintaining is so easy – it's a simple switch

Product data

General Information		Operating and Electrical	
Light source replaceable	No	Input Voltage	220 to 240 V
Number of gear units	1 unit	Line Frequency	50 to 60 Hz
Driver included	Yes	Power Consumption	13 W
Light source engine type	LED	Power Factor (Fraction)	0.5
Light Technical		Connection	Flying leads/wires
Luminous Flux	1,200 lm	Cable	Cable without plug 2-pole
Luminous Efficacy (rated) (Nom)	92 lm/W	Number of products on MCB of 16 A type B	10
Correlated Color Temperature (Nom)	3000 K	Temperature	
Color rendering index (CRI)	>80	Ambient temperature range	-20 to +40 °C
Light source color	Warm white	Controls and Dimming	
Optic type	Wide beam	Dimmable	No
Optical cover type	Polycarbonate linear	Driver/power unit/transformer	Power supply unit (On/Off)
Luminaire light beam spread	140°	Control interface	-

Essential Smartbright LED Batten

Constant light output	No
-----------------------	----

Mechanical and Housing

Housing Material	Polyamide
Optic material	Polycarbonate
Optical cover material	Polyamide
Fixation material	Steel
Housing Color	White
Optical cover finish	Clear
Overall length	1,185 mm
Overall width	21 mm
Overall height	34.2 mm
Dimensions (Height x Width x Depth)	34 x 21 x 1185 mm

Approval and Application

Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK00 [No protection]
Protection class IEC	Safety class II
Glow-wire test	Temperature 850 °C, duration 5 s
CE mark	-
Warranty period	1 years
EU RoHS compliant	Yes

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
-------------------------	--------

Initial chromaticity	SDCM<7
Power consumption tolerance	+/-10%

Over Time Performance (IEC Compliant)

Median useful life L70B50	20,000 hour(s)
---------------------------	----------------

Application Conditions

Maximum dim level	Not applicable
-------------------	----------------

Product Data

Order product name	BN068C LED12/WW L1200 TH G2
Full product name	BN068C LED12/WW L1200 TH G2
Full product code	911401821397
Order code	911401821397
Material Nr. (12NC)	911401821397
Numerator - Quantity Per Pack	1
Net Weight (Piece)	0.162 kg
EAN/UPC - Product/Case	8710163310671
Numerator - Packs per outer box	24
EAN/UPC - Case	8710163310978

Dimensional drawing

